



# SPECIFICATIONS - AVANT 635



**LIFT CAPACITY**

**1100**


**kg**



**ENGINE POWER**

**37,5**


**hp diesel**



**LIFT HEIGHT**

**2,8**

**m**



**SPEED**

**14**

**km/h**

## SPECIFICATIONS

Length	2550 mm
Width	see table
Height	2035 mm
Weight	1360 + 170 kg
Standard wheels	26x12.00-12"Grass / TR
Transmission, drive	hydrostatic
Pulling force	1200 kp
Drive speed	14 km/h
Aux. hydraulics oil flow / pressure	66 l/min 200 bar
Turning radius inside/outside	900 /2190 mm
Max. lifting height	2835 mm
Tipping load *	1000 kg
Max. breakout force / 50 cm	1250 kg
Engine make and type	Kubota V1505
Engine output (ISO Gross)	28 kW (37,5 hp)
Fuel	Diesel

## WIDTH

Wheel size	Width
27 x 8.50 - 15	1005 mm
23 x 10.50 - 12	1140 mm
26 x 12.00 - 12	1290 mm
320/60 - 12	1290 mm

## HEIGHT WITH CAB

Wheel size	23 x 10.50 - 12	26" wheels & 320/60-12	27 x 8.50 - 15
L Cab	2020 mm	2035 mm	2048 mm
LX Cab	2010 mm	2025 mm	2038 mm
DLX Cab	2030 mm	2045 mm	2058 mm
DLX with A/C on the roof	2166 mm	2181 mm	2194 mm

\*) Load is measured at 400 mm from the attachment coupling plate, including attachment weight (70 kg) and with counterweights.

## DIMENSIONS

