









ELECTRIC BATTERY POWERED

MOTOR: AC 12 kW - 48 V.

TRANSMISSION: automatic, hydrostatic. Max speed 2 km/h.

FRAME: fabricated from preformed and welded steel plate with

built-in counterweight. Standard carry deck.

TRACKED UNDERCARRIAGE: rubber tracks.

BOOM: fabricated from preformed and welded steel plate with 2 hydraulic telescoping sections on nylon wear pads. Incorporated manual extension.

HYDRAULIC SYSTEM: gear pump, electric proportional distributor with remote control, filter, safety valves on all boom operations. Max hydraulic pressure 200 Bar.

TOTAL MACHINE WEIGHT: Kg 2.100.

OPTIONAL EXTRAS: L.M.I. (electronic Load Moment Indicator), man bucket, radio remote control, hydraulic winch, hydraulic chain hoist, manual jib extension, battery, battery charger, non-marking tracks.

DIESEL POWERED

ENGINE: diesel HP 16,5 - 4 cylinders, water cooled.

TRANSMISSION: automatic, hydrostatic. Max speed 2 km/h.

FRAME: fabricated from preformed and welded steel plate with builtin counterweight. Standard carry deck.

TRACKED UNDERCARRIAGE: rubber tracks.

BOOM: fabricated from preformed and welded steel plate with 2 hydraulic telescoping sections on nylon wear pads. Incorporated manual extension.


HYDRAULIC SYSTEM: gear pump, electric proportional distributor with remote control, filter, safety valves on all boom operations. Max hydraulic pressure 200 Bar.


TOTAL MACHINE WEIGHT: Kg. 1.900.

OPTIONAL EXTRAS: L.M.I. (electronic Load Moment Indicator), man bucket, radio remote control, hydraulic winch, hydraulic chain hoist, manual jib extention, LPG conversion.

The crane complies with following international standards: - DIN 15018 (1,3) - 15019 (1) class H 2 B3 - ANSI - 1994 5m - 98/37/CE - 89/336/CEE 4 3 2 1 2 3 4m

MODEL 20 TRX









- I.S.P.E.S.L.



