

Leguan 225.



225

Leguan 225.

225

22.5 m
max. working height

11.2 m
max. side reach

250 kg
max. lift capacity

All-terrain spider lift with unrivaled performance.

INDUSTRY-LEADING all-terrain capabilities, a high-profile track platform and fast driving speeds make the next-generation Leguan 225 a perfect choice for even the most demanding environments. The spider lift's boom is designed to maximize side reach even at high working heights, and a smart control interface guarantees quick and smooth movements.

Thanks to our user-friendly joystick controls, controlling the boom structure is steady and simultaneous movements come naturally. The Leguan 225's smart features reduce malfunctions and increase efficiency so that you can focus on the project at hand. The boom is shielded from external blows, falling branches and sawdust, making the 225 a great choice for arborists and construction workers alike.



Standard features.

- 21 hp Kubota diesel engine + 230 V electric motor
- 230 V and USB power outlets on platform
- Automatic engine RPM control
- Automatic start-stop function for electric motor
- Automatic levelling of the outriggers
- Proportional outreach monitoring system
- Electric rotation of the platform
- Home function / Back to work position function
- JIB-boom with 120-degree operating range
- Battery powered emergency lowering system
- Lower controls with integrated service display
- Signal horn

Optional features.

- Remote control for driving and outriggers
- LED spot lights for platform
- Tool trays on platform
- Outrigger beacons
- Hose to platform (air/water)
- Engine heater
- Non-marking tracks
- Narrow single person platform
- Leguan special trailer

Technical features.

| | |
|--|--|
| Max. lift capacity | 250 kg (2 persons) |
| Max. working height | 22.5 m |
| Max. platform height | 20.5 m |
| Max. outreach | 9.1 m (250 kg) – 11.2 m (120 kg) |
| Transport dimensions, L x W x H | 6.03 x 1.33 x 2.2 m |
| Platform dimensions | 1.33 x 0.75 m |
| Rotation of the platform | 110° (±55°) |
| Slewing | 360° |
| Gradeability | 45% (25°) |
| Dimensions w/o platform, L x W | 5.27 x 1.25 m |
| Outrigger support dimensions | 4.08 x 4.08 m |
| Max. slope for outriggers | 25 % (14°) |
| Weight | 2,950 kg |
| Engine | Kubota 21 hp diesel or 230 V / 2.2 kW electric |
| Drive system: hydraulic | tracks |
| Max. drive speed | 3.1 km/h |