



AS50e

Electric rammers

Emission-free - For all classic rammer work

With the battery tamper, the operator works completely free of emissions. The battery-powered rammer is not only an asset when compacting soil in trenches and city centres, but also relieves the operator and the environment on every construction site. One battery charge is sufficient to do all the work of an average working day. The battery can be changed without tools in just a few easy steps and can be used for a wide range of other Wacker Neuson construction equipment.

Highlights

- Low energy costs
- No exhaust emissions
- Maintenance-free electric motor
- Starts with a push of a button
- One battery for all products

Technical Data

Electrical - Output Det	ails	Operating weight	71.0 kg
Nominal current	41.00 A	Stroke at tamper	39.0 mm
Nominal voltage	51.0 V	Motor	
Nominal power [P]	2.10 KW	Motor type	Asynchronous motor
Mechanical - Output Details		Environment Data	
Number of blows	680.0 1/min	Degree of protection	IP23D
Area capacity	147.0 m2/h	Storage temperature range	-30 - 50 °C
Forward Running	8.8 m/min	Operating temperature range	0 - 45 °C
Power of impact	16.0 kN	Sound power LWA, guaranteed	108.0 dB(A)
Mechanical Details		Sound power LWA (Standard)	EN 500-4
Length	610.0 mm	HAV summation (average value)	7.7 m/s2
Length Ramming Shoe	340.0 mm	HAV summation (Standard)	EN 500-4
Width	363.0 mm	Operating Fluids	
Width Ramming Shoe	280.0 mm	Oil specification	SAE 10W-40
Height	1,050.0 mm	Oil volume	0.700 l
Weight	61.50 kg	Lubrication intervall	250.0 h

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.