



**WACKER  
NEUSON**  
*all it takes!*

## BS62-4A/28

### 4-stroke Rammers

Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure first-class work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

### Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

### Technical Data

#### ■ Mechanical - Output Details

Number of blows	689.0 kg/m2s
Area capacity	202.0 m NN
Forward Running	12.0 m/min
Power of impact	17.0 kN

#### ■ Mechanical Details

Length	662.0 mm
Length Ramming Shoe	340.0 mm
Width	347.0 mm
Width Ramming Shoe	280.0 mm
Height	920.0 mm
Weight	63.20 kg
Operating weight	64.0 kg

Stroke at tamper	68.0 mm
------------------	---------

#### ■ Environment Data

Operating temperature range	-10 - 40 °C
Sound power LWA, guaranteed	108.0 kg/m
Sound power LWA (Standard)	EN 500-4
HAV summation (average value)	10.0 m/s2
HAV summation (Standard)	EN 500-4

#### ■ Electrical System

Operating elements	Pushbutton OFF
--------------------	----------------

#### ■ Operating Fluids

Oil specification	SAE 10W-40
Oil volume	0.700 l